

YOUR BEST PARTNER IN PACKAGING

The new Delta RotaVac® system seamlessly integrates Ilapak's Delta 6000 flow-wrapper with an innovative rotary vacuum chamber that is optimised for applications whether fresh primal meat cuts, retail, food service or cheese products. This has created a highly efficient and labour saving solution for replacing more expensive pre-made shrink bags with lower cost film from a reel.

Reduce labour by 60% versus pre-made bag solutions, thanks to the labour reducing, fully integrated solution llapak Delta RotaVac $^{\otimes}$.





TECHNICAL SPECIFICATIONS


Line Speed	Up to 60cpm. Production output dependent upon product, film and system specifications.	
Product Dimensions		
LENGTH	Up to 650mm - 25.6"	
WIDTH (INTENDED AS PRODUCT HALF CIRCUMFERENCE)	320mm - 12.6" (jaws 350m -13.7") 420mm - 16.5" on request (jaws 450mm 17.7")	
HEIGHT	Up to 230mm - 9", with small product traps	
Film Cut-Off	Up to 630mm - 24.8" Cut-off defined as: product length+(height x 1.2)+28mm (1.1"), depending on product characteristics.	
Wrapping Materials	Shrink barrier films, laminated, co-extruded and all sealable films.	
Film Reel Dimensions		
coreØ	76.2mm - 3" standard 152.4mm - 6" on request	
outerØ	400mm - 15.7" standard"	
WIDTH	800mm - 31.5" 900mm - 35.4" available as an option	
Film Reel Max Weight	Depending on film reel width, up to 75 kg - 165 lbs	
Electronic Platform	Allen Bradley control platform. Other electronic platforms on request.	
Power Requirement	From 220 to 480V, 50/60 Hz, 3-phase,	
Compressed Air	6 bar	
Machine Weight	4500 kg	

MAIN FEATURES

BENEFITS

Fully integrated solution	•	Higher output Less labour Reduced handling & reduced leakers Increased OEE % Zero unfilled bags Greater film savings per pack
Optimised design for Pork, Beef, Lamb	>	Maximise your throughput per sq ft/mtr Avoid product accumulation Minimise film use Maximise floorspace
ilaPredict maintenance package	>	Predictive maintenance to avoid breakdown Minimise TOC (total cost of ownership) Minimise downtime,
Hygienic modular design	•	Reduce bacterial risk Minimise cleaning time
Validated on major film suppliers	>	Krehalon, Bemis, Coveris, Cryovac
Delta Mode	>	Reduce maintenance with reduced cycle count Ramp up/down based on production Save energy





All measurements not specified in inches are given in millimeters. Please discuss your needs with our local representative to configure these machines to your product's specific requirements. These specifications are not binding. We reserve that right to change them without prior notice.

Discover more about us, visit: